

PROPERTIES & CHARACTERISTICS

Product: Termination Bar 2263

Material: 6063-T4 Aluminum Alloy

Thickness: .063" (14 gauge)

Dimensions: 1" (25 mm) x 10' (3 m) long

Top Lip: 1/4" (6.35 mm) bent at a 45 degree angle

Weight: 24 lbs. (11 kg) bundle

Holes: 1/4" (6.35 mm) holes spaced 8" (2.44 m) on center



Packaging

25 pcs; 250 lf (76.2 m) pieces per bundle

Availability

For immediate availability and distributor locations call 800.610.3906 or email info@invergellc.com

Description

Termination Bar 2263 is designed to be installed at the upper end of a fluid applied, single-ply application, or a peel and stick product. The top 1/4" is designed to hold the manufacturer recommended sealant to help seal locations for TPO, PVC, EPDM, and fluid applied systems. This termination bar can be fastened using concrete anchors, nails or equivalent. The manufacturer's specification sheet must be consulted to ensure that the termination bar is installed per manufacturer's specification. Inverge is not responsible for the waterproofing of the assembly it's being installed on.

Warranty

Inverge warrants Termination Bar 2263 to be free of defects only at the time of shipment from the manufacturing facility. Inverge cannot warranty the method of application, nor the waterproofing of any assembly. The installing contractor must install this term bar according to the waterproofing manufacturer's specification. Inverge warranties to replace or refund, at its option, any termination bar proven to be defective; but is not responsible for any loss or damage. The dollar value of Inverge's liability will not exceed the purchase price of the termination bar.

